



Product Number: 873

Product Name: Pure Raw Linseed Oil

USE AND SAFETY INFORMATION

General Use Suggestions: Apply to raw wood only (except for additional coats and natural rubbed finishes). Linseed Oil should penetrate the wood to be effective. Mix two parts Sunnyside Mineral Spirits or Sunnyside Specs Paint Thinner with one part Linseed Oil. Mix only enough for each application. Always wipe off excess after allowing 5 to 10 minutes to penetrate. Wood finished with Linseed Oil can be further finished with paste wax, polyurethane or alkyd varnish. When used outside on fences, barns, silos, and porous type wood, apply without thinning. It is not necessary to wipe excess oil off. Tools and equipment should be cleaned with Sunnyside Specs Paint Thinner or Mineral Spirits.

DANGER: RAGS, STEEL WOOL OR WASTE SOAKED WITH RAW LINSEED OIL MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER. The time frame and conditions under which materials may spontaneously catch fire are unpredictable. If rags or other application materials (including any materials containing linseed oil mixtures) are to be set aside, even for short periods of time, they should be placed in sealed, water-filled metal containers until final disposal. Do not take internally. Do not transfer to unlabeled containers.

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

KEEP OUT OF REACH OF CHILDREN.