VOC COMPLIANT LACQUER THINNER TECHNICAL DATA SHEET 477



SUNNYSIDE VOC COMPLIANT LACQUER THINNER

DESCRIPTION

VOC Compliant Lacquer Thinner is the recommended lacquer thinneer and clean up solvent when a low VOC thinner is required. Fast evaporating and extremely flammable.

ITEM NUMERS & SIZES

 Pint
 Quart 47732
 1-Gallon 477G1
 2.5-Gal. 477G5
 5-Gal. 477G5
 55-Gal. 477G5

HAZARDOUS INGREDIENTS

Ingredient CAS# Acetone 67-64-1 Parachlorobenzo-

trifluoride 98-56-6 2-Butoxyethanol 111-76-2

SAFETY INFORMATION

 HEALTH:
 2

 FIRE:
 3

 REACTIVITY:
 1

PRODUCT APPLICATION

VOC Compliant General Purpose Thinner effectively thins most oil based paints, stains and varnishes. Use for clean up after painting.

PHYSICAL PROPERTIES

Typical Properties GRAVITY, (60 °F)	Results
API	
SPECIFIC	0.85
DENSITY (Lb./GAL)	7.08
DISTILLATION RANGEE IBP ° F	133
FREEZING POINT, °F (°C)	
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	0
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR (Ptt-Co) Max.	5
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY (as Acetic Acid)	
ALKALINITY (AS NH3, WT%)	
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Characteristic, Nonresidual
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt% WATER MISCIBILITY	Partial
DOT SHIPPING NAME	Paint related material
DOT CLASSIFICATION	Hazard Class III
SHIPPING Wt. at 20 °C	7.08
V.O.C. (g/L)	24 g/L
v.o.o. (g/L)	27 y/L

These properties are repesentative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

ASTM Applied D-278 D-1298 ■

TEST METHOD

D-86
D-1133
D-611
D-56

D-1255 D-156 ■ D-484 D-130 D-1353

D-1614 D-1296

D-847

D-1218 D-1266

D-1364 D-1722

See MSDS sheeet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html