

BACK TO NATURE



LEAD-CLEAN™

Lead Dust Cleaner & Paint Deglosser

TECHNICAL DATA SHEET

I. Description: Lead-Clean™ is a water-based, biodegradable, lead dust cleaner & paint deglosser. A **special NON-TSP formula eliminates lead dust**, the most common cause of lead poisoning. Lead-Clean is designed to hold lead in solution for effective removal. It is also an excellent multipurpose cleaner on dirt, stains, grease, grime and unwanted marks. It is designed to react quickly and work efficiently. It is specifically engineered to have excellent wetting action to better penetrate surface soils. As a post paint removal product, it insures effective, time saving clean-up. Lead-Clean is also two products on one. For use prior to lead paint encapsulation, let it dwell longer and a special deglossing agent helps insure proper adherence.

II. Instructions:

A. Use as a Lead Dust & Multi-purpose cleaner

1. As a Household lead dust cleaner, Lead-Clean should be used full strength. As a commercial lead dust cleaner, multi-purpose cleaner, or post paint removal clean-up product, Lead-Clean may be used full strength or diluted up to 3 to 1 with water.
2. Apply Lead-Clean using a cloth, sponge, trigger spray or garden type sprayer for larger areas.
3. Wipe Lead-Clean onto the surface - work in with a brush or pad for stubborn areas. Allow to dwell on the surface for up to 5 minutes.
4. Wipe down with a wet sponge/cloth and let dry.
5. When repainting after paint removal, let dry approximately 1 Hour before applying new finish.
6. Hepa vacuum where necessary. Inspect visually and with wipe sample where necessary.
7. Use second application when necessary. As a lead dust cleaner, do not reuse applicators.

B. Use as a Paint Deglosser

1. As a paint deglosser, Lead-Clean should be used full strength.
2. Clean off surface dirt using a damp cloth.
3. Apply Lead-Clean using a cloth, sponge, trigger spray or garden type sprayer for larger areas.
4. Work Lead-Clean into the surface using brush or pad if necessary. Allow Lead-Clean to dwell on the surface approximately 10-15 minutes.
5. While surface is still wet, wipe down with a dry cloth. If Lead-Clean has dried on the surface, wipe down with a wet sponge and allow to dry.
6. Let dry approximately 1 hour before applying encapsulant or new finish.
7. Inspect visually. Do test patch where necessary.
8. Use second application when necessary.

C. Coverages: Full Strength: 400-450 sq. ft.,
Diluted 1-1 (makes 2 gals) 800-900 sq. ft.,
Diluted 2-1 (makes 3 gals): 1200-1350sq. ft.,
Diluted 3-1 (makes 4 gals): 1600-1800 sq. ft.

III. Safety Instructions: Safety goggles or face shield are recommended for eye protection. Protective gloves such as neoprene, nitrile gloves are also recommended. In case of eye contact flush with plenty of cool water for 15 minutes, lift lids, do not rub. Get medical attention. In case of ingestion-drink water or milk to dilute. Do not induce vomiting. Get medical attention immediately.

KEEP OUT OF REACH OF CHILDREN
Dispose of properly.