

PREMIUM CLEANER/DEGREASER CONCENTRATE
CHALLENGER
 PC-737
 WATER SOLUBLE NON-ABRASIVE BIODEGRADABLE

TACKLES EVERY CLEANING CHALLENGE!

Walls, Floors, Doors, Windows, Concrete, Tile, Grout, Siding, Outdoor Furniture, Grills, Engines, Heavy Equipment, Auto, Waste Containers... Cleans Soot, Grease, Oil, Dirt, Paint, Mildew Stains.



GENERAL INFORMATION

Challenger PC-737 is a strong concentrate that can be diluted with water. When diluting, your best guideline to follow is "the greasier the surface the more **Challenger** you'll need in the mix."

To apply Challenger: First spray the surface to be cleaned with **Challenger**. Give the **Challenger** a little time to penetrate the grease and grime. Then rinse well with water (preferably hot or warm, but cold water also works well).

EXTERIOR USES

Concrete Surfaces / Garage Floors: Use full strength on driveways and sidewalks. Allow **Challenger** to work 5-10 minutes. Flush with a pressure washer or hose, with warm or hot water.

Aluminum Siding: Spray the siding with 25% **Challenger** and 75% water. Rinse the water using a pressure washer or hose. Test **Challenger** on siding before applying. Rinse from the bottom up to prevent streaking.



Outdoor Furniture (man-made materials): Spray the furniture with a 50% mixture of **Challenger** and 50% water. Rinse with water by hand or hose.

Barbeque Grills: Spray **Challenger** full strength onto grilling surfaces and allow to work for 1-2 minutes, then rinse well. To degrease exterior surface, use a 50% mixture of **Challenger** and water. Rinse well.



Lawn Mowers and Golf Carts: Use a dilution of 25% to 50% **Challenger** depending on the amount of grime on the surface. Always test painted surfaces in an inconspicuous place first. Allow **Challenger** to work for 1-2 minutes then rinse with warm or cold water.



INTERIOR USES

Tile and Linoleum Floors: For most tile and linoleum floors, a solution of 25% **Challenger** and 75% water will work well. If floors are waxed, test the dilution to make sure it is not removing the wax. If you want to remove the wax, use a stronger dilution, then rinse.

Fireplace Doors: Spray **Challenger** full strength. Allow to penetrate for 1 to 2 minutes. Rinse with warm water.

Walls: Wash walls with a solution of 10% **Challenger** and 90% water. Also excellent as a wall wash before painting. No rinsing necessary. Very greasy walls, such as restaurant kitchens, require a stronger mixture such as 50% **Challenger** and 50% water or maybe stronger. Always test **Challenger** on painted walls before using.

Desks, Tables, Vinyl Chair Seats, File Cabinets, etc.: If desks and chairs are extremely dirty, use a solution of 50% **Challenger** and 50% water, then rinse with water.

If used on wood, use a mild solution of 20% **Challenger** and 80% water and apply with a soft cloth. Rinse surface with clean, damp cloth. Always test **Challenger** on wood before using.

Windows: Use 10% **Challenger** and 90% water. Do not rinse.

Sinks and Showers: Spray full strength directly on surface. Allow **Challenger** to work for 1 to 2 minutes. Rinse with warm or cold water. Rinse thoroughly before entering the shower or tub to prevent slipping.

Grout: A 50% mixture of **Challenger** and water cleans grout. Test first, if the grout is sealed — **Challenger** could remove the sealant.

Magic Marker and Spots: Spray with 50% **Challenger** and 50% water. Use a sponge and rinse with water. Test **Challenger** on carpeting before using.

EQUIPMENT AND OTHER INDUSTRIAL APPLICATIONS

Air Conditioning Coils: Spray with 50% **Challenger** and 50% water. Flush with water.

Heavy Equipment, Trucks, Forklifts, and Air Compressors: Exterior Surfaces: 25% **Challenger** and 75% water. Flush with water. Engines: Use full strength. Allow **Challenger** to work for 10-15 minutes, then flush with water.



Warehouse Floors: Use full strength on concrete. Allow **Challenger** to work for 10-15 minutes. Flush with a pressure washer or hose.



Restaurant Filters: Apply **Challenger** straight and allow **Challenger** to work for 10 minutes. Then flush with hot water using a pressure washer. If filters are extremely greasy, spray **Challenger** on filters and then place in a plastic bag for one hour before flushing with water.

Garbage Cans and Dumpsters: Spray **Challenger** full strength or dilute to 75% **Challenger** and water. Rinse with water using a pressure washer or hose.

Helpful Hints: For really tough jobs, such as baked on grime, place the item in a sealed plastic bag overnight. When working with fiberglass, wet the fiberglass first then apply the **Challenger** solution. Don't be afraid to experiment. A 50/50 mixture works wonders on white wall tires, grease spots on clothes, and cleans pitch on saw blades.

Product	Size	Item No.	Case Wt.	Pack	UPC #
Challenger	32 Oz. Spray	73732	28 lbs.	12	7-19818-22332-6
Challenger	Gallon	737G1	42 lbs.	4	7-19818-22101-8
Challenger	5 Gallon	737G5	47 lbs.	1	0-76542-00521-6

